

	900MHz WIRELESS MIC SYSTEM		
			201
	2		201

•SYSCOM()

102


A/S

OPERATING
INSTRUCTIONS

Wireless Microphone System

RECEIVER : SRX-910 (10CH)

TRANSMITTER : STX-910 (10CH)



가 481-10 2 617 618

TEL : (02) 861-1961 4 FAX : (02) 861-1975

E-mail : kep@syscomk.co.kr

- 1. SYSTEM
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.

1. SYSTEM

SYSCOM 6mm Camcorder
19" Rack Type
Transmitter() Receiver()
928.250~929.750MHz
SYSCOM
가

Transmitter


- 1) : 925.125MHz ~ 937.500MHz
- 2) : ± 15 PPM
- 3) RF : 10mW
- 4) : 60Hz ~ 15kHz (±3dB) (RX+TX)
- 5) : 90dB (RX+TX)
- 6) : PLL Synthesizer
- 7) (1K) : 0.6% (RX+TX)
- 8) 가 : 10CH
- 9) : Whip Antennna
- 10) : 5
- 11) : DC 3V (AA" 1.5V X 2)
- 12) (Case) : 63 X 102 X 19 (mm) , ±5%
- 13) : 100g (Without Batteries)

Receiver


- 1) : 3μV
- 2) : 60Hz ~ 15kHz (±3dB) (RX+TX)
- 3) : 90dB (RX+TX)
- 4) FM : 60K
- 5) (1K) : 0.6% (RX+TX)
- 6) : -20dBm ~ -10dBm (ADJ.)
- 7) 가 : 10CH
- 8) : Whip Antenna
- 9) : 5
- 10) : DC 3V (AA" 1.5V X 2)
- 11) (Case) : 63 X 102 X 19 (mm) , ±5%
- 12) : 100g (Without Batteries)

7.


6mm Camcorder



A/V SYSTEM



2.



* Wind Screen : SPW-052


3.

6mm Camcorder

- 1) 10 가
- 2) RF
- 3) (BK-720S) Camcorder Shoe
- Handycam
- Receiver
- Accessory
- 4) (Compander Type)
- (Dynamic Range) S/N(Signal To
- Noise)
- 5) 가 (Limiting Circuit)
- 가
- 6)
- 가
- 7) Case Poly Carbonate 가
- ABS
- Noise
- protective Panel Handling Noise
- 8)

4)

가





- 1) "AF OUT" (3.5")
- MIC
- (AC-XLR35 AC-3535)
- 1) SP-05() "MIC"
- 1) RECEIVER() ON
- Power. indicator가
- 2) 가
- RF Fizzing
- (" ")
- 가
- 가


6.

- 1) , OPEN
- 2) (⊕ ⊖ OFF)

- 1) (BK-720S) 가 shoe



- 2) BK-720S ()
- 3) (가) BK-720S




4.

- 1) (Battery) 가 (Alkaline)
- 2) (PWR) ⊕ ⊖
- 3) (PWR)
- 4) RF 가 EMI
- 5) (Battery)
- 6)
- 7) 가

5.

1) RECEIVER



SRX-910

Channel Selector


Audio Output
JACK

Power. indicator
Battery

LED Lamp가

(PWR)

2) TRANSMITTER



MIC

Connector

Gain Control

MIC

Speech, , Dynamic Range

Channel Selector

.10ch 가

(.)

STX-910 ANT

Power. indicator

Battery

LED Lamp가

(PWR)

